

VIGIL Video Management Suite v11.5

VIGIL Server software, now 64-bit, is the core service all other 3xLOGIC applications are built upon. With our Easy Setup Wizard to guide you through installation, you will be up and running in minutes. Designed with limited bandwidth in mind, Server utilizes our proprietary RapidStream Technology and Substream Motion Detection capabilities to provide high resolution over low bandwidth networks. Server is compatible with all ONVIF Profile S cameras, which includes 3xLOGIC's Time of Flight, Thermal, and V- and S-Series cameras, new VISIX Gen III cameras, as well as boasting a large library of more than 150 Point-of-Sale integrations.

VIGIL Client gives you unrivaled access to live and recorded video from any of your networked VIGIL Server NVRs. Advanced playback and intelligent SmartSearch™ functionality lets you identify and review events of interest quickly and easily. Seamless infinias Access Control integration allows for a complete solution encompassing the full line of 3xLOGIC's products, giving our customer's a powerful but easy-to-use surveillance and access control network.

Additional software packages are available, including POS, Video Analytics Reporting, and VCM for centralized health monitoring and management. Download our free mobile app, View Lite II for your Android or iOS device.

New in VIGIL v11.5

Along with standard stability and performance improvements across the entire VIGIL VMS suite, VIGIL 11.5 has introduced several new features and additions to an already powerful toolset, all with the end user in mind.

- **VIGIL Server** - Conversion to a 64-bit service, VISIX Gen III Support Including new 3xLOGIC Camera Setup Utility-B
- **VIGIL Client** - Dual Color Themes, VISIX Gen III Video Stream Settings Access via Client UI, Live Viewer UI Improvements
- **VIGIL VCM** - New Monitoring Criteria, Monitor Rec. Cam Functionality Expanded, New Suspend Job Feature, User Persistent Column Ordering and Widths Across Entire VCM application.



Introducing in VIGIL 11.5...

VISIX Gen III Support



Image Resolution and Format:

IP Resolution: All Standard Resolutions/Megapixel/ HD Megapixel/Panoramic

IP Video Formats: Standard 3:4, 16:9, 180° and 360°

Minimum Hardware Requirements for VIGIL Client:

CPU: Intel® Core™ i3 Processor

RAM: 4GB (8GB if running Virtual Switch)

GPU: PCI Express 2GB (4GB Recommended)

Minimum Hardware Requirements for VIGIL VCM Server*:

CPU: Intel® Core™ i7 Processor

RAM: 16GB

HDD: 500GB SATA (Minimum 500MB required for install)

Database (Optional): MSSQL2014 Express (or other SQL2014 variant)

Supported Operating Systems:

OS: Windows 7, Windows 8.1, Windows 10

*Stated VCM requirements are for enterprise-level networks. Refer to the VIGIL VCM User Guide for minimum requirements for smaller networks.